



InnoviFastTM

2-1/4 in. XHD Seam Plates (14-Barb)

System Compatibility

InnoviFast 2-1/4 in. XHD Seam Plates (14-Barb) are intended for use with IKO InnoviTPO Roofing Systems and are approved for use with an appropriate IKO Diamond Shield Limited Warranty. Building owners, specifiers, roof consultants and roofing contractors are invited to review the IKO InnoviTPO System Specifications at www.iko.com/comm for further information on including this product as part of a complete IKO roofing system.

Excellent Attachment for TPO Membranes

InnoviFast 2-1/4 in. HD Seam Plates (14-Barb) have 14 barb anchors, along with reinforcing ribs, for strong wind uplift performance when used for roof system attachment to steel and wood roof decks. Stamped from 22 ga. steel with Galvalume coating, InnoviFast 2-1/4 in. XHD Seam Plates (14-Barb) are intended for use with InnoviFast HD Fasteners, Purlin Fasteners, Concrete Drive Pins, and other approved IKO fastening products.

Stock #: 6300126

OD: 2-1/4 in. (60.3 mm) round

Thickness: 0.0328 in. (1 mm)

Finish: AZ50 Galvalume®

Pail Weight: 40.6 lbs. (18.4 kg)

Quantity/Pail: 1,000

All reported values are nominal.

- Used to attach reinforced single-ply and modified bituminous membranes to the roof substrate.
- 14 barb anchors, along with reinforcing ribs, for strong wind uplift resistance.
- 22 ga. 50% aluminum-zinc alloy coated steel.

The information on this sheet is based on data supplied by the manufacturer to IKO and believed to be true and accurate. The information is offered solely for the user's consideration, investigation and verification. Nothing contained herein constitutes or represents a warranty or guarantee for which the manufacturer or the distributor can be held legally responsible. Galvalume® is a registered trademark of BIEC International, Inc.



6300126 ©2025 IKO Commercial - All rights reserved. 03/25