



## RESIDENTIAL INFORMATION BULLETIN

August 2020

No. R-53

### HUBER® ENGINEERED WOODS LLC ZIP SYSTEM™ ROOF SHEATHING

This will confirm IKO roofing products are approved for use with the ZIP System™ Roof Sheathing and will carry the full IKO limited warranty, provided the following installation requirements are followed:

1. The deck is 1/2" minimum thickness or TECO/CANPLY rated oriented strand board (OSB).
2. The ZIP System is applied in strict accordance with the specifications and guidelines of Huber® Engineered Woods LLC.
3. Apply IKO shingles in accordance with the instructions printed on each bundle wrapper.
4. When reroofing involves a tear off, apply one layer of #15 or #30 non-perforated asphalt saturated underlayment or synthetic underlayment over the entire roof deck.
5. For low slopes 2:12 up to 4:12, follow these guidelines:
  - a. For new construction – apply one layer of ICE AND WATER PROTECTOR applied according to instructions supplied with each roll, or 1 layer of asphalt saturated felt (or equivalent).
  - b. When reroofing involves a tear off – apply one layer of ICE AND WATER PROTECTOR, applied according to instructions, or alternately, apply 2 layers of asphalt saturated felt (or equivalent), the first sheet overlapping the eave protection by 19", followed by full 36" widths overlapping each preceding course by 19".
6. IKO will not be responsible for deficiencies or movement in the roof deck, manufacturing defects of the fasteners, and/or improper application of the substrate or IKO asphalt shingles.

For information regarding the ZIP System™ Roof Sheathing or the application guidelines, please call 800-933-9220 or visit their website at [www.huberwood.com/zip/](http://www.huberwood.com/zip/).

For additional information on any of IKO's products or application requirements, visit us on the web at [www.iko.com](http://www.iko.com), or contact us in Canada at 1-888-766-2468, or the United States at 1-888-456-7663.